

JET

LINHA PESADA



Type	ELECTRICAL SPECIFICATIONS			Weight (Kg)	DIMENSIONS L x W x H (mm)		
	C20 (Ah)	RC (Minutes)	CCA -18°C				
JET - FREE MAINTAINANCE							
J90 CD/CE	90	160	470	21,6	296	162	225
J90 SD/SE	90	160	550	23,1	354	175	190
J100 GR 31	100	180	550	26,5	330	173	240
J135 MD/ME	135	235	680	38,1	510	215	232
J150 MD/ME	150	305	800	40,0	510	215	232
J170 MD/ME	170	330	810	43,0	510	215	232
J180 MD/ME	180	340	830	44,0	510	215	232
J180 SC	180	330	810	43,5	505	220	217
J200 ON	200	360	950	53,0	515	275	232
JET FREE - SEALED							
JF90 CD/CE	90	160	470	21,6	296	162	225
JF90 SD/SE	90	160	550	23,1	354	175	190
JF100 GR31	100	180	550	26,5	330	173	240
JF135 MD/ME	135	235	680	38,1	510	215	232
JF150 MD/ME	150	305	800	40,0	510	215	232
JF170 MD/ME	170	330	810	43,0	510	215	232
JF180 MD/ME	180	340	830	44,0	510	215	232

HEAVY DUTY



The **JET HD (heavy Duty)** series offer great power and endurance for vehicles with the latest equipment and high electrical requirements. Our improved plate construction provides high starting power and endurance suitable for all classes of vehicles, including vans, agricultural vehicles, tractors and buses. The range is available in completely sealed and spill-proof.

MAIN BENEFITS - HEAVY DUTY SERIES

- Complete range for vans, agricultural vehicles, tractors, HGVs, coaches and buses;
- Wide range of available specifications;
- Vibration proof;
- Low rate of self discharge;
- Improved Endurance;
- Enhanced Safety and reliability.